LCS-8560A
external Modem
Data, Fax, TAM

The LCS-8560A Modem for RS-232 interface. This Modem LCS-8560A uses advanced Agere chipset solution that provides complete system design featuring Voice/Data/TAM modem for 56K Internet access. LCS-8560A offers easy installation and cost-effective connection for SOHO and residential users.

Features:

- Plug and Play compatible for easy installation and configuration
- Data transfer rate up to 56 Kbps download and up to 48 Kbps upload
- V.92 and V.44 compatible
- Friendly GUI configuration and management software
- Supports fax function with transfer rate up to 14.4 Kbps
- Supports telephone answering machine (TAM) function and telephony services
- Supports Video conferencing

Specifications:

Standard:	ITU-T V.92/90 56.000b/s
Chipset:	Agere
Datarates:	56.000 Kbit/s Download, 48.000 Kbit/s Upload
Data Mode:	ITU-T V.92, V.90, V.34, V.32 bis, V.32, V.22 bis, V.22, V.23, V.21, Bell 212A and Bell 103
Data Compression:	ITU-T V.44, V.42 bis/MNP 5
Error Correction:	ITU-T V.42/MNP 2-4
Voice Mode:	Telephone Answering Machine(TAM), DTMF detection & generation,
Video Support:	H.324, V.80 (Video Conference Protocol)
Fax Mode:	ITU-T V.17, V.29, V.27 ter, V21 Ch2, Group 3, Class 1
Fax Transfer Rate:	Up to 14.4 Kbps send and receive
Media Connector:	Power Switch, RJ-11, RS232
Interface:	RS-232
Certificate:	FCC part 15, part 68, CE
Power Consumption:	562mW max.
Dimensions:	124mm x 87mm x 28mm, 165g
Workaround:	Temperature 0°C ~ 60°C Humidity 5% ~ 95% (non-condensing)
Minimum Requirements:	Pentium compatible processor 233 MHz and above Minimum 32 MB RAM, Minimum 30 MB available hard disk space, CD-ROM drive, RS232 port
Box contains:	Modem, Wire + Plug, Quigg, CD with Driver/Software
EAN:	4016621008246